

Pride® Scooters

"END-TO-END" SOLUTIONS

Footnotes

1. Solid tires available on most models.
2. Varies with user weight, terrain type, battery charge, battery condition and tire pressure.
3. Battery weight not included.
4. HCPCS code KO899 does not meet SADMERC requirements.
5. Battery pack total weight is 27 lbs. each.
6. Due to manufacturing tolerances and continual product improvement, this specification can be subject to variance of + or - 3%.
7. Battery pack is 21 lbs.
8. Durable solid plastic
9. Deep cycle (AGM or gel cell type recommended)
10. 12 AH battery pack weighs 21 lbs.; 17 AH battery pack weighs 33 lbs.
11. Standard with power elevating seat
12. Up to 13 miles with optional 17 AH batteries
13. All shroud panels included



	Go-Go® ULTRA X TRAVEL SCOOTER ⁴	Go-Go® ELITE TRAVELLER™	Revo®	Sonic®	Rally®	Sundancer® ¹¹	Legend®	Celebrity® X	Victory®	Maxima	Legend® XL ⁴	Wrangler® ⁴ PMV	Hurricane® ⁴ PMV
Front Tires ¹	2" x 8" SOLID (3W) 2" x 7" SOLID (4W)	2" x 8" SOLID (3W) 2" x 7" SOLID (4W)	2" x 8" SOLID	2" x 7.5" SOLID	2" x 8"	2.5" x 9" SOLID	3.5" x 10"	3.5" x 10"	3.5" x 10"	3" X 10" SOLID	4" x 13"	6" x 13"	4" x 13"
Rear Tires ¹	2.5" x 8" SOLID	2.5" x 8" SOLID	3" x 9" SOLID	2.5" x 7.5" SOLID	2.5" x 9"	2.5" x 9" SOLID	4" x 10"	4" x 10"	3.5" x 10"	4" X 10" SOLID	4" x 13"	6" x 13"	4" x 13"
Maximum Speed ²	UP TO 4.25 MPH	UP TO 4.25 MPH	UP TO 4.5 MPH	UP TO 4.25 MPH	UP TO 4.25 MPH	UP TO 4.5 MPH	UP TO 5.75 MPH	UP TO 6 MPH	UP TO 5 MPH	UP TO 5.25 MPH	UP TO 5.8 MPH	UP TO 5/10 MPH	UP TO 4.5/9 MPH
Ground Clearance ⁶	2.625" (3W) 2.5" (4W)	2.625" (3W) 2.5" (4W)	2.25"	1.75"	3"	3.5"	3.5"	3.5"	4"	4.5"	4"	7"	4"
Turning Radius (3-wheel) ⁶	32.5"	32.5"	38"	34"	39"	38"	41"	41.5"	41"	52"	N/A	N/A	N/A
Turning Radius (4-wheel) ⁶	43.25"	43.25"	50"	N/A	54"	N/A	54"	54"	54"	54"	65"	77"	65"
(3-wheel) Length/Width ⁶	36.5"/19.25"	36.5"/19.25"	43"/21.5"	37"/21"	41"/21"	41.625"/23.25"	45.375"/24"	46"/24"	47"/24"	46.25"/25.5"	N/A	N/A	N/A
(4-wheel) Length/Width ⁶	39.75"/19.25"	39.75"/19.25"	44.75"/21.5"	N/A	44"/21"	N/A	47"/24"	46.75"/24"	48"/24"	46.875"/25.5"	52"/24"	63.5"/31"	52"/24"
Seat to Ground Height Range	20.5"-22"	20.5"-22"	23"-25"	20"-21"	20"-22"	18"-23"	22"-25"	23"-24.25"	21.5"-23.5"	22"-24"	23"-26"	27.75"-31.75"	23"-26"
Seat Type (standard)	COMPACT, FOLDABLE (17"X17")	COMPACT, FOLDABLE (17"X17")	FOLDABLE MOLDED PLASTIC (18"X16")	FOLDABLE MOLDED PLASTIC (18"X16")	FOLDABLE MOLDED PLASTIC (18"X16")	DELUXE, CONTOURED LOW-BACK (17"X16")	CRS DELUXE RECLINING HIGH-BACK W/SLIDERS & HEADREST (18"X18")	DELUXE MOLDED PLASTIC W/ SLIDERS (19"X16")	FOLDABLE MOLDED PLASTIC (18"X16")	DELUXE CONTOURED MEDIUM-BACK (22"X18.5")	CRS DELUXE RECLINING HIGH-BACK W/SLIDERS & HEADREST (18"X18")	DX CONTOURED HIGH-BACK WITH ADJ. HEADREST & SLIDERS (18"X16")	CRS DELUXE RECLINING HIGH-BACK W/SLIDERS & HEADREST (18"X18")
(3/4-wheel) Weight ³	71 LBS./76 LBS.	75 LBS./79 LBS.	106.5 LBS./125 LBS.	97.5 LBS./N/A	93 LBS./116 LBS.	148 LBS./N/A	155 LBS./166 LBS.	141.5 LBS./151 LBS.	110.5 LBS./116.5 LBS.	175 LBS./184 LBS.	N/A/207 LBS.	N/A/216 LBS.	N/A/209 LBS.
Seat to Deck Height Range	15"-16.5"	15"-16.5"	16.25"-18.25"	14"-15"	16.5"-18.5"	15.5"-20.5"	17"-20"	16.25"-17.5"	17"-19"	16"-18"	16.5"-19.5"	19"-23"	16.5"-19.5"
Battery Weight Requirements ⁹	9 LBS. EA. ⁷	9 LBS. EA./14 LBS. EA. ¹⁰	24.5 LBS. EACH ⁵	9 LBS. EACH	14 LBS. EA./24.5 LBS. EA.	24.5 LBS. EACH	24.5 LBS. EACH	24.5 LBS. EA./32.5 LBS. EA.	24.5 LBS. EACH	24.5 LBS. EA./38 LBS. EA.	38 LBS. EACH	63.5 LBS. EACH	38 LBS. EACH
Per-Charge Range (max.) ²	(2) 12AH	(2) 12AH OR (2) 17AH	(2) U-1	(2) 12AH	(2) 17AH OR (2) U-1	(2) U-1	(2) U-1	(2) U-1 OR (2) 40AH	(2) U-1	(2) U-1 OR (2) NF-22	(2) U-1 OR (2) NF-22	(2) GROUP 27	(2) U-1 OR (2) NF-22
Battery Charger	UP TO 10 MILES	UP TO 10 MILES ¹²	UP TO 20 MILES	UP TO 10 MILES	UP TO 25 MILES	UP TO 20 MILES	UP TO 25 MILES	UP TO 25 MILES	UP TO 25 MILES	UP TO 30 MILES	UP TO 30 MILES	UP TO 25 MILES	UP TO 30 MILES
Suspension	OFF-BOARD 2A	OFF-BOARD 2A	OFF-BOARD 5A	OFF-BOARD 2A	ON-BOARD 3A	ON-BOARD 3A	ON-BOARD 3A	OFF-BOARD 5A	ON-BOARD 3A	OFF-BOARD 5A	OFF-BOARD 5A	ON-BOARD 5A	OFF-BOARD 5A
Maximum Weight Capacity	N/A	N/A	N/A	N/A	N/A	N/A	REAR	(3-WHEEL) REAR (4-WHEEL) FRONT AND REAR	N/A	REAR	FRONT AND REAR	REAR	FRONT & REAR
Standard Body Colors	250 LBS. MAX	260 LBS. MAX	300 LBS. MAX	300 LBS. MAX	300 LBS. MAX	300 LBS. MAX	350 LBS. MAX	350 LBS. MAX	350 LBS. MAX	500 LBS. MAX	400 LBS. MAX	400 LBS. MAX	400 LBS. MAX
Available Power Elevating Seat	RED, BLUE ⁸	RED, BLUE, SILVER ¹³	RED, BLUE	RED, BLUE ⁸	CANDY APPLE RED, VIPER BLUE	CANDY APPLE RED, VIPER BLUE	CHAMPAGNE, CANDY APPLE RED, VIPER BLUE	CANDY APPLE RED, VIPER BLUE	CANDY APPLE RED, VIPER BLUE	CANDY APPLE RED, VIPER BLUE	CHAMPAGNE, CANDY APPLE RED, VIPER BLUE	CANDY APPLE RED, VIPER BLUE	CANDY APPLE RED, VIPER BLUE
Weight of Heaviest Piece	N/A	N/A	N/A	N/A	N/A	STANDARD	YES	YES (SPECIAL ORDER)	N/A	YES (SPECIAL ORDER)	YES (SPECIAL ORDER)	YES (SPECIAL ORDER)	YES (SPECIAL ORDER)
	28 LBS. (3-WHEEL) (FRONT SECTION) 33 LBS. (4-WHEEL) (FRONT SECTION)	28 LBS. (3-WHEEL) (FRONT SECTION) 33.5 LBS. (4-WHEEL) (FRONT SECTION)	48 LBS. (3-WHEEL) (REAR SECTION) 51.5 LBS. (4-WHEEL) (FRONT SECTION)	35 LBS. (FRONT OR REAR SECTION)	45 LBS. (3-WHEEL) (REAR SECTION) 45 LBS. (4-WHEEL) (FRONT/REAR SECTION)	71 LBS. (REAR SECTION)	61 LBS. (REAR SECTION)	56 LBS. (3-WHEEL) (FRONT SECTION) 65.5 LBS. (4-WHEEL) (FRONT SECTION)	50 LBS. (REAR SECTION)	64 LBS. (3-WHEEL) (REAR SECTION) 72.5 LBS. (4-WHEEL) (FRONT SECTION)	82 LBS. (REAR SECTION)	N/A	82 LBS. (FRONT SECTION AND REAR SECTION)
	TRAVEL	PORTABLE	MID-SIZE LUXURY	FULL-SIZE LUXURY	HEAVY-DUTY	PMVs							