

C2000

C2000 is a high-end outdoor wheelchair with power and endurance. The innovative servo steering allows for safe driving over long distances, including inclinations and uneven terrain. At the same time, it makes the C2000 manoeuvrable, which is crucial when it is used indoors. The suspension of the entire chassis with the selection of the proper seat ensures a secure driving experience, including in bends and on uneven terrain.

What is special about me?

- Innovative servo steering allowing individual movement of the casters

Standard Model

- 6 km/h
- enAble50 control unit
- 94 Ah (C5) gel batteries
- Range up to approx. 50 km
- Standard seat, small or large
- Innovative chain steering
- Luggage carrier
- 14" caster wheels
- Suspension on all wheels
- Individual centre footrests
- Splash guard for all wheels
- Frame colours: Sky blue, Stainless steel silver, Sparkle red, Sparkle light orange, Jet black RAL 9005

Options

- 10 km/h
- Special controls: chin, foot, sip-and-puff, attendant control
- Environmental control
- Standard seat, XL
- Contour seat small/large, XL
- Electric seat height adjustment, 400 mm
- Power seat tilt
- Electric back angle adjustment
- Various footplates for different areas of application/weights
- Other custom colours available subject to a surcharge
- Heavy-duty load of over 200 kg

Quality for life



Technical Data

Speeds	6 or 10km/h
Battery Capacity	94 Ah (c5) gel batteries
Range under test conditions approx.	50km
Control unit	enAble50 (130 A)
Max user weight	160, optionally 200kg
Max. obstacle negotiation height	100mm (rear-wheel drive)
Climbing ability	17%
Length including footplates	116 / 1390mm
Width	680mm
Turning radius	980mm
Seat height (without cushion), At 3° seat tilt	470 530 mm (front / rear wheel drive)
Seat width	380 – 560mm
Seat depth	380 – 500mm (standard seat) 360 – 480mm (contoured seat) 380 – 560mm (Recaro seat)
Back angle	-9° to +30°
Seat tilt	30° or 45°, electric
Back height	450 / 500 / 550mm
Armrest height	255 – 350mm
Lower leg length	250 – 540mm (standard seat) 280 – 540mm (contoured seat)