

Our Lightest Aluminium Travel Scooter



One of the lightest aluminum travel scooter on the market! Experience the convenience of a a lightweight, compact travel scooter with airline safe batteries. Easy to put into the boot, with its heaviest piece weighing only 11 kg. The Apex Aluma-Lite, with its aluminium frame, weighs only 28.8 kg making it our lightest four wheeled scooter yet!



**WEIGHS ONLY
28.8 kg**



**FLIGHT SAFE
BATTERIES**

PRIDE[®]
MOBILITY PRODUCTS LTD.
LIVE YOUR BEST*

www.pride-mobility.co.uk



Specifications

| | |
|--|---|
| Weight Capacity | 18 stone 13 lbs (120 kg) |
| Maximum Speed ¹ | Up to 4 mph |
| Ground Clearance ³ | 32 mm (1.25") |
| Turning Radius ³ | 1385 mm (54.5") |
| Overall Length ³ | 1022 mm (40.25") |
| Overall Width ³ | 490 mm (19.25") |
| Max. Obstacle Climb | 57.5 mm (2.25") |
| Drive Tyres | 203 mm (8") front & rear - solid |
| Suspension | N/A |
| Total Weight Without Batteries ^{3, 4} | 28.8 kg (63.4 lbs) |
| Heaviest Piece When Disassembled ³ | 11.2 kg - rear main frame 9.5 kg - front frame 8.9 kg - seat 2.5 kg - battery pack |
| Drivetrain | 24v single motor |
| Dual Breaking System | Regenerative & electromechanical |
| Battery Requirements ³ | 12 Ah Lithium Battery |
| Battery Weight ⁴ | 3.5 kgs (8 lbs) |
| Battery Charger | 2 amp off-board |
| Colour | Red, Blue & Black |

Features

- Disassembles into 5 pieces
- Airline friendly batteries
- Lightweight aluminium frame
- 8" alloy style wheels
- Easy-to-grip tiller adjustment knob
- Spacious foot platform
- Additional stability for a more secure ride
- Simple and easy to use control system



Available in:

- Red
- Blue
- Black



¹ Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition, and tyre condition. This specification can be subject to a variance of (+ or -) 10%.

² Includes standard seat weight.

³ Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or -) 3%.

⁴ Battery weight may vary based on battery manufacturer.

NOTE: All specifications subject to change without notice. The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or - 3%. Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.