

# Colt TWIN

HIGH-PERFORMANCE OPERATION  
AND ALL-NEW FEATURES

## COLT TWIN

The sleek, sporty **Colt Twin** Scooter delivers high-performance operation and features unique dual front wheels for the maximum stability of a four-wheel scooter with the superb manoeuvrability of a three-wheel scooter. The Colt Twin has a full complement of advanced standard features like exclusive low-profile tyres, a wraparound delta tiller, and feather-touch disassembly.



(Images are for illustration purposes only)




**Pride**<sup>®</sup>  
Mobility Products Ltd.  
— LIVE YOUR BEST<sup>™</sup> —

(Tel) 01869 324 600 • (Fax) 01869 323 070 • [www.pridemobility.co.uk](http://www.pridemobility.co.uk)

# Colt Twin

Weight capacity:	25 Stone (158.75 kg)
Maximum speed <sup>1</sup> :	Up to 4 mph (6.4 km/h)
Ground clearance <sup>2</sup> :	5.7 cm (2.25")
Turning radius <sup>2</sup> :	106.7 cm (42")
Overall length <sup>2</sup> :	116 cm (46")
Overall width <sup>2</sup> :	56 cm (22")
Tyre size:	Front: Dual 23 cm (9") solid Rear: 25 cm (10") solid
Suspension:	N/A
Total weight without batteries <sup>5</sup> :	62.5 kg (138 lbs.)
Heaviest piece when disassembled:	Front section: 27.2 kg (60 lbs.)
Standard seating:	Type: CRS Junior Seat Weight: 19 kg (42 lbs.) Material: Black Vinyl Dimensions: 44.45 cm (17.5") overall width 43.18 cm (17") effective depth
Seat-to-deck range:	44.5 cm - 48.3 cm (17.5" - 19")
Drive system:	Rear-wheel drive, sealed transaxle, 24-volt DC motor
Dual braking system:	Regenerative and electromechanical
Battery requirements <sup>3</sup> :	Two 12-volt, deep cycle Size: (2) 31-36 AH or 40-45 AH Weight <sup>4</sup> : 31-36 AH: 9.8 kg (21.5 lbs.) 40-45 AH 14.74 kg (32.5 lbs.) each
Battery charger:	5-amp, off-board

Colours:



## Features

- Dual front wheels for added stability
- Exclusive one-hand feather-touch disassembly provides the ultimate quick transport system
- Auto-connecting front-to-rear harness
- Delta tiller with wraparound handles
- Exclusive stylish, lightweight, non-marking, low-profile wheels
- Backlit battery gauge
- Long-lasting, high-intensity LED headlight offers optimal pathway illumination
- Includes pinchless hinges & eight-position seat rotation
- Easy-grip tiller adjustment knob
- Easy access tiller-mounted charger port for standard dual-voltage off-board charger

## Options

- Forearm crutch holder
- Cane/crutch holder
- Oxygen tank holder
- Rear basket
- Safety flag
- Walker holder

<sup>1</sup> Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tyre condition. This specification can be subject to a variance of + 10%, -5%.

<sup>2</sup> Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or - 3%).

<sup>3</sup> AGM or gel cell type required.

<sup>4</sup> Includes standard seat.

<sup>5</sup> Battery weight may vary based on manufacturer.

<sup>6</sup> Tested in accordance with ISO 7176-22, 2000 and ISO 7176-11, 1992 standards.

The information contained herein is correct at the time of publication; due to the manufacturer's commitment to constant improvement and development, they reserve the right to alter specifications without prior notice.

NOTE: This product conforms to all applicable ANSI/RESNA testing requirements and ISO 7176 series EN12184 standards. All specifications subject to change without notice.



32 Wedgwood Road, Bicester, Oxfordshire OX26 4UL  
(Tel) 01869 324 600 • (Fax) 01869 323 070 • [www.pridemobility.co.uk](http://www.pridemobility.co.uk)

**Pride**<sup>®</sup>  
Mobility Products Ltd.  
— LIVE YOUR BEST —



**PRIDE**<sup>®</sup>  
PERFORMANCE MOBILITY  
— LIVE YOUR BEST —