

Sleek, Sporty Undeniably Stylish



GO GO
ELITE TRAVELLER *SPORT*



It's time to make your mark on this world! The Go-Go® Elite Traveller Sport offers simple disassembly and an ergonomic delta tiller, perfect for one-handed operation. Enjoy the versatility of this sporty scooter, as well as bright LED lighting.

PRIDE[®]
MOBILITY PRODUCTS LTD.
LIVE YOUR BEST*

www.pride-mobility.co.uk

Specifications


Weight Capacity	23 st 3 lbs (147 kg)
Maximum Speed ¹	Up to 4 mph
Ground Clearance ³	38 mm (1.5") at motor
Turning Radius ³	1283 mm (50.5")
Overall Length ³	1092 mm (43")
Overall Width ³	540 mm (21.25")
Max. Obstacle Climb	50mm (2")
Drive Tyres	229 mm front & rear - solid
Suspension	-
Total Weight Without Batteries ^{3, 4}	44 kg (100 lbs)
Heaviest Piece When Disassembled ³	20 kg (44 lbs)
Drivetrain	24 volt DC motor
Dual Breaking System	Regenerative & electromechanical
Battery Requirements ³	2 x 18 Ah deep cycle or 2 x 20 Ah deep cycle
Battery Weight ⁴	18 Ah - 12.5 kg (27.4 lbs) 20 Ah - 20 kg (44 lbs)
Battery Charger	Off-board
Colour	Red & blue

Features

- Feather-touch disassembly with one hand
- Front and rear LED lighting
- Wrap around delta tiller
- Extra 2" of space for added leg room
- Includes 2 sets of interchangeable shrouds
- Exclusive & stylish low profile tyres
- Convenient front basket

Available in:

- Red
- Blue



¹ Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition, and tyre condition. This specification can be subject to a variance of (+ or -) 10%.

² Includes standard seat weight.

³ Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or -) 3%.

⁴ Battery weight may vary based on battery manufacturer.

NOTE: All specifications subject to change without notice. The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or - 3%. Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.