

Sporty. Sophisticated. Unique. The Jazzy Select® 6 offers superior suspension for powerful performance and stability. Experience a tight turning radius and a depth-adjustable seat. Life can be complicated, yet the Jazzy Select 6 is simple.







Specifications

Weight Capacity	21 st 6 lbs (136 kg)
Maximum Speed ¹	Up to 4 mph
Ground Clearance ³	70 mm (2.75")
Turning Radius ³	521 mm (20.5")
Overall Length ³	1022 mm (40.25") with front riggings
Overall Width ³	622 mm (24.5")
Max. Obstacle Climb	70 mm (2.75")
Drive Tyres	3556 mm (14") solid
Suspension	ATX Suspension (Active-Trac with extra stability)
Total Weight Without Batteries ^{3, 4}	56.1 kg (123.6 lbs)
Heaviest Piece When Disassembled ³	56.1 kg (123.6 lbs)
Drivetrain	Two motor, mid-wheel-6 drive
Dual Breaking System	"Intelligent Braking" electronic regenerative, disc park brake
Battery Requirements ³	2 x 12v, deep cycle NF-22 batteries
Battery Weight ⁴	16.9 kg (37.2 lbs) each
Battery Charger	8 Amp off-board
Colour	Red & Blue

Features

- Intuitive controller is easy to operate
- ATX Suspension with Mid-Wheel 6 Technology
- Depth-adjustable, limited-recline, fold-flat, high-back seat
- Flip up, heigh-adjustable foot platofrm offering two positions of heigh and one position of depth.
- Colour-through shroud

Also available in:

- Blue
- Red





NOTE: All specifications subject to change without notice. The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or -3%. Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.



¹ Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition, and tyre condition. This specification can be subject to a variance of (+ or -) 10%.
2 Includes standard seat weight.

³ Due to manufacturing tolerances and continual product improvement,

this specification can be subject to a variance of (+ or -) 3%.

Battery weight may vary based on battery manufacturer.