





# **Specifications**

DRIVE WHEELS	35.5 cm (14") (pneumatic or solid available)
CASTORS	Front: 23 cm (9") (pneumatic)
ANTI-TIPS	7.6 cm (3") solid (rear)
MAXIMUM ALLOWABLE INCLINE	10.5% (6°)
SUSPENSION	
	Active-Trac® ATX Suspension (with long trail arm)
MAXIMUM SPEED 1	Up to 4 mph (6.4 km/h)
BRAKES	Intelligent braking (electronic, regenerative disc brakes)
GROUND CLEARANCE	7.62 cm (3")
TURNING RADIUS	65.4 cm (25.75")
OVERALL SIZE	Length: 88 cm (35") Width: 63.5 cm (25")
DRIVETRAIN BATTERIES BATTERY CHARGER AVAILABLE	Synergy® (standard seat) Adjustable Width: 35.5 cm - 51 cm (14"-20") Adjustable Depth: 35.5 cm - 51 cm (14"-20") Synergy® TRU-Comfort Adjustable Width: 41 cm - 51 cm (16"-20") Adjustable Depth: 41 cm - 51 cm (16"-20") Euro Seat 2 Only available in the following sizes: Adjustable Width: 41 cm - 51 cm (16"-20") Adjustable Depth: 41 cm - 51 cm (16"-20") Two-motor, rear-wheel drive Two 12 volt, deep cycle 70 AH (Group 24) 8A, off-board
ELECTRONICS	R-Net LED
WEIGHT CAPACITY	21 Stone 6 lbs. (136 kg) maximum (user weight)
BASE WEIGHT	58.51 kg (129 lbs.)
BATTERY WEIGHT <sup>4</sup>	70 AH (Group 24): 23.13 kg (51 lbs.) (each)
WARRANTY	Lifetime limited warranty on frame; 1-year limited warranty on electronics; 18-month warranty on drive control system; 2-year limited warranty on drivetrain

## **Shroud Colour**



Apple Red



Blue





Black





Silver

### **Features**

- Narrow 25" (63.5 cm) width and compact 35" (88 cm) length (without foot riggings)
- Outstanding tight space manoeuvrability
- Maximum speed up to 4 mph (6.4 km/h)
- High-performance, high-efficiency motor package
- Accepts rehab seating
- Swing-away joystick
- Accomodates full range of Quantum<sup>®</sup> seating and accessories
- Sliding battery tray for easy access

## **Options**

- Power tilt
- Power recline
- Manual ELRs
- Power ELRs
- Headrest

- Comfort seating
- Waterfall armrests
- Euro Seat 2
- TRU-Balance® Power Postioning System
- Kerb climber

#### FOOTNOTES:

- 1) Varies with base model, user weight, terrain type, battery amp hour rating (Ah), battery charge, battery condition, motors, controller type, tyre type and tyre condition. This specification can be subject to a vaciance of +10%, -5%.
- 2) Due to manufacturing tolerances and continual product improvement, this specification can be subject to variance of + or -3 %
- 3) Without foot riggings.
- 4) Battery weight may vary based on manufacturer.
- 5) Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory
- 6) AGM or gel cell type required.

The information contained herein is correct at the time of publication; due to Pride's commitment to constant improvement and development, we reserve the right to alter specifications without prior notice.

NOTE: This product conforms to all applicable ANSI/RESNA testing requirements and ISO EN12184 standards. All specifications subject to change without notice.



32 Wedgwood Road, Bicester, Oxfordshire OX26 4UL (Tel) 01869 324 600 (Fax) 01869 323 070 www.quantumrehab.co.uk



