

Utprovad av:

E-post:

Utprovad för:

Telefon:

Datum:

Save the guide to the desktop and open it from there.

Bambino 3 has an adjustable rear axle. To find a balance that suits you the rear axle can be adjusted into different positions. Note desired measure at "Settings". Bambino 3 has a seat height of 41 cm in the front and 39 at the rear, without cushion. To adjust the seat height you can chose other rearwheel sizes or a raising Kit with suitable castor fork from theList of options.
Max userweight: **60 kg** for **seat width 24-27**

Spara guiden på "skrivbordet" och öppna den med **Adobe Reader**, för bästa funktion
Välj utförande på din rullstol genom att klicka i cirkelarna i denna guide.
Blå, understruken text är klickbar för att **visa info** eller bild.
BB = sittbredd, **HH**= rygghöjd

Original design

Alternative options

Other options

[info](#)

1) Chassis-colour

- Blue** - Racing Blue
- Black** - Anodic Black
- Clear

Optional colour - A higher price and

- longer delivery time for optional colour, Fyll i art.no. in the square



2) Seat width (BB)

[art.no.](#)

- Clear

24 cm

27 cm

Art.no includes chassis, seat, backrest lock, anti-tip device, With 24" rear wheels anti-tip device +30 mm is mounted.



3) Backrest adjustable height

- [20-28 cm blue](#) 27-35 cm blue
- 523BB17 523BB18
- [20-28 cm black](#) 27-35 cm black
- 523BB17BL 523BB18BL
- Clear

4) Rear axle

- [Carbon](#) 6 dgr
- 33030BB
- Rensa

[Carbon](#) 6 dgr +10 mm

33031BB

With 20" rearwheels +120 mm castors

[Other](#) rear axle or seat height

[Increase the seat height](#)

art. _____



5) Castor and fork

- [120 mm](#)
- [art.no.](#) With 20" rear wheels you need to raise the rear axle 10 mm
- Clear

[90 mm](#)

[art.nr.](#)

Standard with 20" rearwheels

[Other castor fork](#)

[Excel guide](#) art. _____



6) Footrest

[Footrest B3](#) - foldable, angle adjustable

42341BB

- Clear



7) Brake

- [Brake B3](#)
- 4630200
- Rensa

Brake B3 moved forward

4630300

With 24" rear wheels

[Brake blade](#) B3 PU tire SET

4630234



8) Rear wheel - without pushrim

- 22" [Standard](#)
- [art.no.](#)
- Clear

20" [Standard](#)

[art.no.](#)

24" [Standard](#)

[art.no.](#)

[Rear wheel size](#)

[Other rear wheels](#)

art. _____



Tire - choose tire

- [Schwalbe Right Run](#) 20",22",24"
- Clear

[Rugged](#) 24"

Schwalbe [Marathon Plus](#) 22",24"

[PU](#) 20",22",24" (massive)



9) Pushrim

[Titanium](#)

190DD11 (x2 / wheelchair)

- Clear **DD** = Wheel diameter

[Paragrip](#)

19051DDBT x2

[Tetragrip](#)

19052DDBTx2

[Maxgrip](#) 24" (contains latex)

1903070 x2 (20")
1903080 x2 (22")
1903060 x2 (24")



Accessories

Side guard



- [Side guard B3](#), short
4235010
- Clear

Arm support



- [Arm support B3](#) short
with side guard
4401410
- Adjustable in height in 3 pos.

Seat width adaptor



- [Seat width adaptor](#)-pair
4235020
- Seat width adaptor-left
4235021
- Seat width adaptor-right
4235022
- Clear

Limits the back rest angle forward to 16 mm
Narrows the seat width 7,5mm on each side.

Lateral support



- [Lateral support B3](#) adjustable cpl
4236000 /pcs
- Left Right
- Position
- Standard Standard
- Narrow -9mm Narrow -9mm



Push bar

- [Push bar B3](#)
4233000

Height, angle adjustable
with Quick release



Head support

- [Head support B3 Blue](#)
4710100
 - Head support B3 Black
4710100BL
 - Clear
 - Position Low Position High
- Height, angle and depth adjustable

Cushion Wedge cushion



- [2,5 cm](#)
572BB25
- [5 cm](#)
575BB25
- Clear
- [Wedge cushion](#)
57710BB
not width 24 cm

Attachment pelvic belt

- Attachment plate pelvic belt cpl
9900247 backrest 2 point attachment
- Attachment clamp pelvic belt pair
9900248 2-point attachment
- [Attachment pelvic belt 4-p](#) plate + clamp
9900250 4-point attachment
- Attachment pelvic belt 4-p with clamps
9900248 x 2 4-point attachment

Spoke protectors



- Clear
- [24" Panthera logo](#) 4500000
- [22" Panthera logo](#) 4500100
- [20" Panthera logo](#) 4500021



- [24" Without logo](#) 4500011
- [22" Without logo](#) 4500111



- [24" Splash](#) 4500324
- [22" Splash](#) 4500322
- [20" Splash](#) 4500320



- [24" Car rim](#) 4500124
- [22" Car rim](#) 4500122
- [20" Car rim](#) 4500120



- [24" Animal Planet](#) 4500424
- [22" Animal Planet](#) 4500422
- [20" Animal Planet](#) 4500420



- [24" Smiley](#) 4500224
- [22" Smiley](#) 4500222
- [20" Smiley](#) 4500220

* Tube protection front; Can be too long if footrest is in its high position.
Fits when rear axle is at std balance and footrest at low pos. 16 cm or lower,
high pos. 28 cm or lower, from floor to top of footplate.



Other

- [Tube protection front](#) (chassis tube) *
9900251 (2 pcs)
- [Tube protection rear](#) (backrest tube)
9900251 (1 pcs) Not with pushbar
- [Backrest wedge](#) _____ pcs
4710012
- [Tray-table](#)
6810000
- [Magnetic holder](#) on rearwheel for tray table
6810010
- [Torso strap](#)
4380238 Chose art.no. for Freewheel according to the **footrest height**
of the wheelchair
Read more about Freewheel on the [homepage](#)
- [Freewheel](#)
- [Freewheel-kit](#) assembly parts
42342BB



Settings

Backrest angle



Note the measure (A) for desired backrest angle. 14-28mm.
Standard=18 mm

A= _____ mm

Rear axle adjustment



Note the measure (A) for desired balance.
Standard=87 mm

A= _____ mm

Footrest position



Note the height measure from the floor, (A) or (B) for the footrest.

[Bambino footplate with Freewheel - info](#)

A= _____ mm B= _____ mm

At 22" rear wheels
Measure high pos. 210-310 mm
Measure low pos. 150-220 mm

Note depth-position:

Std position

Moved forward position 30 mm

Note height-position:

High position

Low position

Transport marking

- YES do mark the wheelchair with attachment points for transport in disabled service
Art.no.9000152

NOTE! See the manual for more information.

Extra