Dermaramp® Relocatable external ramps

A concept which totally transforms wheelchair access, the Permaramp range is designed to be easily adjusted and fixed down or left in place for every type of threshold.

Cut away kerbs • Easy installation • Extremely durable

- Great for semi-permanent access
- Avoid big installation projects and construction mess
- Can be left in place as long as required then re-used elsewhere
- Unique Gripdeck™ surface for incredible grip and sustained outside use Quick and strong access solutions





utilityramp[™] Industrial/commercial portable ramps





Instant installed ramp solution available in 2 widths and 6 lengths

These excellent installed type, semi-permanent relocatable ramps, provide unmatched value and weight capacity.








Your benefits:

Unique Gripdeck™ surface for incredible grip and sustained outside use

Excellent for wooden door thresholds

Contrasting colour safety edge strips increase visibility

Available in standard 76cm width and Superwide 90cm width: perfect for single outward opening doors, and a great bariatric ramp solution



Well suited for scooters, mobility devices and sports wheelchairs

Up to 400kg (63 stone) capacity!



Designed, Manufactured & Stocked in the UK





Key Product Information

For help selecting length see Ramp Guide P4&5

Code Length		Width Capacity		Weight	
PO9	90cm (3ft)	76cm (30ins)	400kg (63st)	8.5kg (19lbs)	
PO12	120cm (4ft)	76cm (30ins)	400kg (63st)	12kg (26lbs)	
PO15	150cm (5ft)	76cm (30ins)	400kg (63st)	15kg (33lbs)	
PO18	180cm (6ft)	76cm (30ins)	400kg (63st)	18.5kg (41lbs)	
PO21	210cm (7ft)	76cm (30ins)	350kg (55st)	22kg (49lbs)	
PO24	240cm (8ft)	76cm (30ins)	300kg (47st)	25kg (55lbs)	
POW9	90cm (3ft)	90cm (35.4ins)	400kg (63st)	10kg (22lbs)	
POW12	120cm (4ft)	90cm (35.4ins)	400kg (63st)	14kg (31lbs)	
POW15	150cm (5ft)	90cm (35.4ins)	400kg (63st)	18kg (40lbs)	
POW18	180cm (6ft)	90cm (35.4ins)	400kg (63st)	22kg (48lbs)	
POW21	210cm (7ft)	90cm (35.4ins)	350kg (55st)	26kg (58lbs)	
POW24	240cm (8ft)	90cm (35.4ins)	300kg (47st)	30kg (65lbs)	

Kerb Height 7cm (3ins)







permaramp®-adjust



Totally adjustable and self-supporting, great for PVC thresholds





This unique self-supporting product requires no fixing to the threshold and eliminates threshold damage.

Your benefits:

Easy height adjustment and installation from above

Designed to clear protruding thresholds and sills

Fix to any firm flat or sloping surface

Telescopic legs can be adjusted to accommodate different threshold types, and give total height adjustment from 7.5cm (3ins) to 25cm (10ins) high

Entry flap accessory available to transition right into the property

> All lengths available in Superwide 90cm option: a great bariatric ramp solution and perfect for single outward opening doors, and extra wide mobility devices



Easy height adjustment and installation from above



Designed, Manufactured & Stocked in the UK







Key Product Information

For help selecting length see Ramp Guide P4&5

	Code Length		Width	Capacity	Weight
	PA9	90cm (3ft)	76cm (30ins)	400kg (63st)	12.5kg (28lbs)
	PA12	120cm (4ft)	76cm (30ins)	400kg (63st)	16kg (35lbs)
	PA15	150cm (5ft)	76cm (30ins)	400kg (63st)	19kg (42lbs)
	PA18	180cm (6ft)	76cm (30ins)	400kg (63st)	22.5kg (50lbs)
	PA21	210cm (7ft)	76cm (30ins)	350kg (55st)	26kg (57lbs)
	PA24	240cm (8ft)	76cm (30ins)	300kg (47st)	29kg (64lbs)
	PAW9	90cm (3ft)	90cm (35.4ins)	400kg (63st)	14kg (22lbs)
	PAW12	120cm (4ft)	90cm (35.4ins)	400kg (63st)	18kg (40lbs)
4	PAW15	150cm (5ft)	90cm (35.4ins)	400kg (63st)	22kg (48lbs)
4	PAW18	180cm (6ft)	90cm (35.4ins)	400kg (63st)	26kg (57lbs)
	PAW21	210cm (7ft)	90cm (35.4ins)	350kg (55st)	30kg (66lbs)
	PAW24	240cm (8ft)	90cm (35.4ins)	300kg (47st)	34kg (75lbs)

Kerb Height 7cm (3ins)



Outward opening doors







permaramp®-entry flap

The ultimate semi-permanent PVC threshold bridging accessory



This bridging flap accessory for the Permaramp®-Adjust means that you can have a ramp fixed in place outside, with a flap that comes down over to the inside of the threshold, giving a smooth transition all the way into the property.

Your benefits:

Hand strap for fast and easy operation

Excellent for sliding and inward opening doors

Unique Gripdeck™ surface on both sides





Code	Length	Width	Capacity	Weight
PE5	45cm (18ins)	72cm (28.3ins)	300kg (47st)	4.8kg (10.6lbs)

NOTE: Only for use with standard width Permaramp-Adjust, ordered separately

utilityramp™





Industrial/Commercial Portable Ramp

Designed and manufactured for commercial use, the Utility Ramp has proved itself in many situations, and has an incredible weight capacity. Longer sizes fitted with wheels for ultimate speed and ease of use.

Your benefits:

Great for wheelchair access or industrial use

Rugged, yet easy to use and portable

Unique Gripdeck™ highly anti-slip surface retains grip even when wet

Up to 400kg weight capacity

Standard 76cm wide or Superwide 90cm wide versions available



3			UF	RW15
1				
	1000	U	1	EXTRA WIDTH
	U			*

Code	Length	Width	Capacity	Weight	
UR9*	90cm (3ft)	76cm (30ins)	400kg (63st)	9kg (20lbs)	
UR12*	120cm (4ft)	76cm (30ins)	400kg (63st)	12.5kg (28lbs)	
UR15	150cm (5ft)	76cm (30ins)	400kg (63st)	15.5kg (34lbs)	
UR18	180cm (6ft)	76cm (30ins)	400kg (63st)	19kg (42lbs)	
UR21	210cm (7ft)	76cm (30ins)	350kg (55st)	22.5kg (50lbs)	
UR24	240cm (8ft)	76cm (30ins)	300kg (47st)	25.5kg (56lbs)	
URW9*	90cm (3ft)	90cm (35ins)	400kg (63st)	10.5kg (23lbs)	
URW12*	120cm (4ft)	90cm (35ins)	400kg (63st)	14.5kg (32lbs)	
URW15	150cm (5ft)	90cm (35ins)	400kg (63st)	18.5kg (41lbs)	
URW18	180cm (6ft)	90cm (35ins)	400kg (63st)	22kg (49lbs)	
URW21	210cm (7ft)	90cm (35ins)	350kg (55st)	26kg (57lbs)	
URW24	240cm (8ft)	90cm (35ins)	300kg (47st)	30kg (66lbs)	
* No wheels. Kerb Height 7cm (3ins)					