

ECO ASSIST

EMPOWER YOUR MOBILITY



REHASENSE

**NEW
PRODUCT**



ECO ASSIST

LIGHTWEIGHT POWER ADD-ON



Eco Assist is the new lightweight power add-on from Rehasense and features a robust construction crafted from high-strength aluminium and steel, a swift 350W motor, and an efficient Li-Ion battery.

Elevate your comfort and safety through customizable controls, dependable brakes, and a sleek design.

Experience the economical and enjoyable way of driving with Eco Assist!

FEATURES AT A GLANCE

- Manual docking system
- Wheelchair fitting width range - 210-480 mm
- Wheelchair clamp fitting height range - 260-420 mm
- Compatible with rigid & folding wheelchairs with a fixed front frame
- Ø160 mm brake disc
- Walk function
- Traction control
- Reverse gear
- Accessory: bigger battery, 48V, 11.6 Ah, 556.8 Wh
- Cruise control (optional)

COLOUR

Black

Front fork: Dark Grey



TECHNICAL DATA

Total weight	Transport weight	Max. user weight	Wheel size	Engine power	Max. engine torque	Speed modes	Max Speed	Climbing power	Standard battery	Driving range
15.5 kg	10 kg	110 kg	12"	350 W	39 Nm	up to 3	20 km/h*	up to 10%	Li-on, 48 V/ 5,8 Ah/ 278 Wh	up to 30 km

* driving speed should be always adapted to country - specific legal regulations.

POWER & LIGHTWEIGHT

Eco Assist provides excellent standard features and a powerful battery. Being so lightweight and compact, the Eco Assist is very easy to transport and store when not in use.


CITY-FRIENDLY DESIGN

With an agile and stylish design, Eco Assist effortlessly navigates urban environments, making every journey in the city a relaxing experience.

SMART FEATURES & DETAILS

Water resistant colour LCD display, Cruise Control, Anti-Slip Traction, LED Headlight and Horn buttons enhance your riding experience, providing a smooth and safe journey.


SPECIAL FEATURES



Twin -brake system: mechanical disc-brake and electric brake




Leg supports are height adjustable to ensure the best fit to the frame min. 260 mm and max. 420 mm



Width Adjustment: use Lever A for easy and quick width adjustment of the clamping jaw. Fitting range width 210 mm to 480 mm



Quick Disconnect to support easier transportation and storage. One simple step is required to connect or disconnect the central locking unit. A safety lock ensures a safe connection



Your Rehasense Dealer

VI-2023



Rehasense's quality management system complies with both the ISO 9001 and ISO 13485 standards, as confirmed by TUV NORD. Rehasense's medical devices are CE-marked and meet the requirements of EU Regulation 2017/745 (MDR.) Rehasense's medical devices are UKCA-marked and meet the requirements of MHRA regulations.

