

RETAIL



				LITE K
Invoice to:			Deliver to:	
Name:			Name:	
Street:		\Box	Street:	
Town:	Postal code:	UK	Town:	Postal code:
E-Mail:		UK	E-Mail:	
Tel:	Fax:	CA	Tel:	Fax:
Order date:			Marked for:	
Purchase order:				
Number required:			Sunrise order no:	
Fax number: +44 (0)845 605 66 89	Base Pricing		Max. user weight:	125 kg
Email: orders@sunmed.co.uk	£1,695		USER WEIGHT	kg
Part no. 84400101 QMA01				
	CLIENT	MEASUREM	ENT	

Seat width (cm)

		34	36	38	40	42	44	46	48
	36	0	0	0	0	0	0	0	0
cm)	38	0	0	0	0	0	0	0	0
depth (cm)	40	0	0	0	0	0	0	0	0
ept	42	0	0	0	0	0	0	0	0
	44	0	0	0	0	0	0	0	0
Seat	46	0	0	0	0	0	0	0	0
	48	0	0	0	0	0	0	0	0
	50	0	0	0	0	0	0	0	0
	Please note	that the me	acurement	is from the h	ack All mas	euromonte :	are in cm an	d without a c	cuehion

Frame Lenç	gth Matrix
Seat Depth	Frame Length
36-40cm	Short
42-44cm	Medium
46-48cm	Long
50cm	Extra long

Please note that the measurement is from the back. All measurements are in cm and without a cushion.

FRONT SEAT HEIGHT SELECTION: independent of front castors and frame versions

Front seat height (cm)

	Fork type (mm)	39	40	41	42	43	44	45	46	47	48	49	50
4"	Short	0	0		0		0						
4	Long				0		0	0		0			
5"	Short	0	0	0	0	0	0	0					
3	Long				0	0	0	0	0		0		
6"	Short	0	0		0	0	0	0	0	0			
0	Long				0	0		0	0	0	0	0	
7"	Long						0	0		0	0	0	0

Max. difference front/ rear seat height: 0 - 110 mm

REAR SEAT HEIGHT SELECTION: independent of rear wheel size

Rear seat height (cm)

Wheels	36	37	38	39	40	41	42	43	44	45	46	47
22"	0	0	0	0	0		0	0	0			
24"			0	0	0		0	0	0	0	0	
25"				0	0	0	0		0	0	0	0

Front Castor

			£
		SEAT UPHOLSTERY AND CUSHIONS	
		Seat Slings	
.RF020001	•	Seat sling, Nylon, tension adjustable	
RF020002		Seat sling, nylon, tension adjustable, 1 utility bag	
.RF020000	0	Without seat sling	
		Seat Cushion with black cover	
_RF020101		Seat cushion, foam (medium-soft), cover with zipper, black, 3cm	85
_RF020102		Seat cushion, foam (medium-soft), cover with zipper, black, 5cm	85
RF020103		Seat cushion, Latex (very soft), cover with zipper, black, 5cm	85
		Jay Cushion - for complete Jay product range see Jay order forms	
JAY020002		JAY Basic	75
JAY020001		JAY Easy Visco C	180
JAY020007		JAY Easy Fluid	415
JAY020004		JAY LITE	290
		Seat accessories	
LRF090018		Lap belt with buckle, metal	70
		BACKREST	
Backrest h	neiaht		
Back heigh	_		
		O 27.5 O 32.5 O 37.5 O 42.5	
		0 30 0 35 0 40 0 45	
		0 00 0 0 0 40 0 40	
LRF030001	•	Backrest tube, aluminium (from BH 27.5cm)	
LRF030015	0	Backrest, angle-adjustable, fold-down	
		○ -12° (78 EU) ○ -8° (82 EU) ○ -4° (86 EU)	
		O 0° (90) EU) O 4° (94 EU) O 8° (98 EU)	
LRF030102		Backrest, angle-adjustable, lock when folded (only with angle adj back)	90
2717 000 702		Push handles	30
LRF030201			
		Push handles long Push handles fold down (aphy from hady beint 20cm)	166
LRF030203		Push handles, fold-down (only from back height 30cm)	165
LRF030204		Push handles, height-adjustable (only from back height 30cm)	220
LRF030205		Push handles, height-adjustable for Jay backs (only from back height 30cm)	220
_RF030200	0	Without push handles	
		Headrest	
LRF030410		Headrest, tall height, depth and angle-adjustable, 23 x 11cm (Only with push handles height adjustable)	245
_RF030411		Headrest, medium height, depth & angle-adjustable, 20 x 11cm (Only with push handles height adjustable)	245
		Backrest upholstery (black)	
_RF030316	0	EXO Backrest sling, padded, adjustable, 1 accessory bag, black (Evo Exo Version)	
		Colour, binding tape: ● Black O Orange O Silver O Red O Blue	
		EXO PRO Backrest sling, padded,adjust., breathable spacer fabric, accessory bag, black (Evo Exo Version)	90
LRF030317		Colour, binding tape: ● Black O Orange O Silver O Red O Blue	
LRF030317		Colour, biriding tape. • Black O Orange O Silver O Red O Blue	

Jay 3 Back - Mid Deep Contour Upper Thoracic: Jay 3 Back - Deep Contour Upper Thoracic: JAY030004 □ Jay Headrest S/A JAY030006 □ Standard Jay head ARMREST AND SID Armrest LRF040050 □ Single-post sideguard, h LRF040051 □ Single-post sideguard, h LRF040052 □ Single-post sideguard, de Sideguards LRF040107 ○ Sideguard, composite, re LRF040102 □ Sideguard, aluminium, ce LRF040103 □ Sideguard, aluminium, fe LRF040104 □ Sideguard, carbon fibre, FRAME LRF010010 ○ Frame FF 75 ° (integrate LRF010011 ○ Frame FF 85 ° (integrate LRF010016 □ Frame SA (removable fo LRF010010 ● Tie down brackets for tra	(choose only one option, not in combination with sideguards; only with 0° and 1° camber) reight-adjustable, removable, armpad (25cm), reight-adjustable, removable, armpad (36cm), repth adjustable, tool height-adjustable, removable, armpad (33cm) (not in combination with armrest) removable, 21 cm high (31cm long), black redord weather protection (in frame colour) (effective seat width is sw + 2cm) render, cold weather protection (black) (effective seat width is sw + 2cm) (fender, cold weather protection (black) (effective seat width is sw + 2cm) (cold footrest)	850 870 290 235 180 180 180 230 315 395
Jay 3 Back - Mid Deep Contour Upper Thoracic: Jay 3 Back - Deep Contour Upper Thoracic: JAY030004 □ Jay Headrest S/A JAY030006 □ Standard Jay head ARMREST AND SID Armrest LRF040050 □ Single-post sideguard, h LRF040051 □ Single-post sideguard, h LRF040052 □ Single-post sideguard, de Sideguards LRF040107 □ Sideguard, composite, re LRF040103 □ Sideguard, aluminium, co LRF040104 □ Sideguard, carbon fibre, FRAME LRF010010 □ Frame FF 75 ° (integrate LRF010011 □ Frame FF 85 ° (integrate LRF010015 □ Frame SA (removable fo LRF090100 ■ Tie down brackets for tra CENTRE OF GRAVI COG23 □ Centre of gravity 2.3cm COG63 □ Centre of gravity 6.3cm COG63 □ Centre of gravity 8.3cm	JAY030021 Medium 46cm	290 235 180 180 180 230 315
Upper Thoracic: Jay 3 Back - Deep Contour Upper Thoracic: JAY030004	JAY030021 Medium 46cm (only with Jay 3 backs)	290 235 180 180 180 230 315
Jay 3 Back - Deep Contour Upper Thoracic: JAY030004 □ Standard Jay head ARMREST AND SID Armrest LRF040050 □ Single-post sideguard, h LRF040051 □ Single-post sideguard, de Sideguards LRF040107 □ Sideguard, composite, re LRF040102 □ Sideguard, aluminium, co LRF040103 □ Sideguard, aluminium, fe LRF040104 □ Sideguard, carbon fibre, FRAME LRF010010 □ Frame FF 75 ° (integrate LRF010011 □ Frame FF 85 ° (integrate LRF010015 □ Frame SA (removable fo LRF010010 □ Tie down brackets for tra CENTRE OF GRAVI COG23 □ Centre of gravity 4.3cm COG63 □ Centre of gravity 6.3cm COG63 □ Centre of gravity 8.3cm	JAY030021 Medium 46cm (only with Jay 3 backs)	290 235 180 180 180 230 315
Upper Thoracic: JAY030004	(choose only one option, not in combination with sideguards; only with 0° and 1° camber) (choose only one option, not in combination with sideguards; only with 0° and 1° camber) (eight-adjustable, removable, armpad (25cm), (eight-adjustable, removable, armpad (36cm), (eight-adjustable, tool height-adjustable, removable, armpad (33cm) (not in combination with armrest) (mot in combination with armrest) (effective seat width is sw + 2cm) (effective seat width is sw + 2cm) (effective seat width is sw + 2cm) (fender, cold weather protection (black) (effective seat width is sw + 2cm) (d footrest) d footrest) d footrest) d footrest) insportation	290 235 180 180 180 230 315
JAY030004 ☐ Jay Headrest S/A JAY030006 ☐ Standard Jay head ARMREST AND SID Armrest LRF040050 ☐ Single-post sideguard, h LRF040051 ☐ Single-post sideguard, h LRF040052 ☐ Single-post sideguard, de Sideguards LRF040107 ☐ Sideguard, composite, re LRF040102 ☐ Sideguard, aluminium, co LRF040103 ☐ Sideguard, aluminium, fe LRF040104 ☐ Sideguard, carbon fibre, FRAME LRF010010 ☐ Frame FF 75 ° (integrate LRF010011 ☐ Frame FF 85 ° (integrate LRF010015 ☐ Frame SA (removable fo LRF090100 ● Tie down brackets for tra CENTRE OF GRAVI COG23 ☐ Centre of gravity 2.3cm COG63 ☐ Centre of gravity 6.3cm COG63 ☐ Centre of gravity 8.3cm	(choose only one option, not in combination with sideguards; only with 0° and 1° camber) (choose only one option, not in combination with sideguards; only with 0° and 1° camber) (eight-adjustable, removable, armpad (25cm), (eight-adjustable, removable, armpad (36cm), (eight-adjustable, tool height-adjustable, removable, armpad (33cm) (not in combination with armrest) (mot in combination with armrest) (effective seat width is sw + 2cm) (effective seat width is sw + 2cm) (effective seat width is sw + 2cm) (fender, cold weather protection (black) (effective seat width is sw + 2cm) (d footrest) d footrest) d footrest) d footrest) insportation	290 235 180 180 180 230 315
ARMREST AND SID Armrest LRF040050 □ Single-post sideguard, h LRF040051 □ Single-post sideguard, h LRF040052 □ Single-post sideguard, de Sideguards LRF040107 ○ Sideguard, composite, re LRF040102 □ Sideguard, aluminium, co LRF040103 □ Sideguard, aluminium, fe LRF040104 □ Sideguard, carbon fibre, FRAME LRF010010 ○ Frame FF 75 ° (integrate LRF010011 ○ Frame FF 85 ° (integrate LRF010015 ○ Frame SA (removable fo LRF090100 ● Tie down brackets for tra CENTRE OF GRAVI COG23 ○ Centre of gravity 2.3cm COG63 ○ Centre of gravity 6.3cm COG63 ○ Centre of gravity 8.3cm	Choose only one option, not in combination with sideguards; only with 0° and 1° camber) reight-adjustable, removable, armpad (25cm), reight-adjustable, removable, armpad (36cm), repth adjustable, tool height-adjustable, removable, armpad (33cm) (not in combination with armrest) removable, 21 cm high (31cm long), black removable, 21 cm high (31cm long), black relight adjustable, removable, armpad (33cm) (not in combination with armrest) removable, 21 cm high (31cm long), black rem	235 180 180 180 230 315
ARMREST AND SID Armrest LRF040050 □ Single-post sideguard, h LRF040051 □ Single-post sideguard, h LRF040052 □ Single-post sideguard, de Sideguards LRF040107 ○ Sideguard, composite, re LRF040102 □ Sideguard, aluminium, co LRF040103 □ Sideguard, aluminium, fe LRF040104 □ Sideguard, carbon fibre, FRAME LRF010010 ○ Frame FF 75 ° (integrate LRF010011 ○ Frame FF 85 ° (integrate LRF010015 ○ Frame SA (removable fo LRF090100 ● Tie down brackets for tra CENTRE OF GRAVI COG23 ○ Centre of gravity 2.3cm COG63 ○ Centre of gravity 6.3cm COG63 ○ Centre of gravity 8.3cm	Choose only one option, not in combination with sideguards; only with 0° and 1° camber) reight-adjustable, removable, armpad (25cm), reight-adjustable, removable, armpad (36cm), repth adjustable, tool height-adjustable, removable, armpad (33cm) (not in combination with armrest) removable, 21 cm high (31cm long), black removable, 21 cm high (31cm long), black relight adjustable, removable, armpad (33cm) (not in combination with armrest) removable, 21 cm high (31cm long), black rem	235 180 180 180 230 315
ARMREST AND SID Armrest LRF040050	(choose only one option, not in combination with sideguards; only with 0° and 1° camber) reight-adjustable, removable, armpad (25cm), reight-adjustable, removable, armpad (36cm), repth adjustable, tool height-adjustable, removable, armpad (33cm) (not in combination with armrest) removable, 21 cm high (31cm long), black old weather protection (in frame colour) (reffective seat width is sw + 2cm) render, cold weather protection (black) (reffective seat width is sw + 2cm) render, cold weather protection (black) (reffective seat width is sw + 2cm) render, cold of footrest) (reffective seat width is sw + 2cm) render, cold of footrest) (reffective seat width is sw + 2cm) render, cold of footrest) (reffective seat width is sw + 2cm) render, cold of footrest) (reffective seat width is sw + 2cm) render, cold of footrest) (reffective seat width is sw + 2cm) render, cold of footrest) (reffective seat width is sw + 2cm) render, cold of footrest) (reffective seat width is sw + 2cm) render, cold of footrest) (reffective seat width is sw + 2cm) render, cold of footrest) (reffective seat width is sw + 2cm) render, cold of footrest) (reffective seat width is sw + 2cm) render, cold of footrest) (reffective seat width is sw + 2cm)	180 180 180 230 315
Armrest LRF040050 □ Single-post sideguard, h LRF040051 □ Single-post sideguard, h LRF040052 □ Single-post sideguard, de Sideguards LRF040107 □ Sideguard, composite, re LRF040102 □ Sideguard, aluminium, co LRF040103 □ Sideguard, aluminium, fe LRF040104 □ Sideguard, carbon fibre, FRAME LRF010010 □ Frame FF 75 ° (integrate LRF010011 □ Frame FF 85 ° (integrate LRF010015 □ Frame SA (removable fo LRF010015 □ Tie down brackets for tra CENTRE OF GRAVI COG23 □ Centre of gravity 2.3cm COG63 □ Centre of gravity 6.3cm COG63 □ Centre of gravity 8.3cm	(choose only one option, not in combination with sideguards; only with 0° and 1° camber) reight-adjustable, removable, armpad (25cm), reight-adjustable, removable, armpad (36cm), repth adjustable, tool height-adjustable, removable, armpad (33cm) (not in combination with armrest) removable, 21 cm high (31cm long), black rold weather protection (in frame colour) render, cold weather protection (in frame colour) (effective seat width is sw + 2cm) render, cold weather protection (black) (effective seat width is sw + 2cm) d footrest) d footrest) d footrest), inset (2cm on each side), active otrest) insportation	180 180 230 315
LRF040050 □ Single-post sideguard, h LRF040051 □ Single-post sideguard, h LRF040052 □ Single-post sideguard, de Sideguards LRF040107 ○ Sideguard, composite, re LRF040102 □ Sideguard, aluminium, ce LRF040103 □ Sideguard, aluminium, fe LRF040104 □ Sideguard, carbon fibre, FRAME LRF010010 ○ Frame FF 75 ° (integrate LRF010011 ○ Frame FF 85 ° (integrate LRF010015 ○ Frame SA (removable fo LRF090100 ● Tie down brackets for tra CENTRE OF GRAVI COG23 ○ Centre of gravity 2.3cm COG43 ○ Centre of gravity 4.3cm COG63 ○ Centre of gravity 6.3cm COG63 ○ Centre of gravity 8.3cm	reight-adjustable, removable, armpad (25cm), reight-adjustable, removable, armpad (36cm), repth adjustable, tool height-adjustable, removable, armpad (33cm) (not in combination with armrest) removable, 21 cm high (31cm long), black cold weather protection (in frame colour) render, cold weather protection (in frame colour) (effective seat width is sw + 2cm) render, cold weather protection (black) (effective seat width is sw + 2cm) d footrest) d footrest) d footrest) d footrest), inset (2cm on each side), active otrest) insportation	180 180 230 315
LRF040051 □ Single-post sideguard, he Sideguards LRF040107 □ Sideguard, composite, resultant learned	reight-adjustable, removable, armpad (36cm), repth adjustable, tool height-adjustable, removable, armpad (33cm) (not in combination with armrest) removable, 21 cm high (31cm long), black old weather protection (in frame colour) (effective seat width is sw + 2cm) render, cold weather protection (in frame colour) (effective seat width is sw + 2cm) (effective seat width is sw + 2cm) d footrest) (LLL from 34cm) d footrest) d footrest), inset (2cm on each side), active otrest) insportation	180 180 230 315
LRF040052 □ Single-post sideguard, de Sideguards LRF040107 □ Sideguard, composite, re LRF040102 □ Sideguard, aluminium, co LRF040103 □ Sideguard, aluminium, fe LRF040104 □ Sideguard, carbon fibre, FRAME LRF010010 □ Frame FF 75 ° (integrate LRF010011 □ Frame FF 85 ° (integrate LRF010015 □ Frame SA (removable fo LRF010015 □ Tie down brackets for tra CENTRE OF GRAVI COG23 □ Centre of gravity 2.3cm COG63 □ Centre of gravity 6.3cm COG63 □ Centre of gravity 8.3cm	epth adjustable, tool height-adjustable, removable, armpad (33cm) (not in combination with armrest) emovable, 21 cm high (31cm long), black old weather protection (in frame colour) ender, cold weather protection (in frame colour) fender, cold weather protection (black) (effective seat width is sw + 2cm) (effective seat width is sw + 2cm) (effective seat width is sw + 2cm) (condition of the seat width is sw + 2cm) (condition of the seat width is sw + 2cm) (condition of the seat width is sw + 2cm) (condition of the seat width is sw + 2cm) (condition of the seat width is sw + 2cm) (condition of the seat width is sw + 2cm) (condition of the seat width is sw + 2cm) (condition of the seat width is sw + 2cm) (condition of the seat width is sw + 2cm) (condition of the seat width is sw + 2cm) (condition of the seat width is sw + 2cm) (condition of the seat width is sw + 2cm) (condition of the seat width is sw + 2cm) (condition of the seat width is sw + 2cm) (condition of the seat width is sw + 2cm) (condition of the seat width is sw + 2cm) (condition of the seat width is sw + 2cm) (condition of the seat width is sw + 2cm) (condition of the seat width is sw + 2cm) (condition of the seat width is sw + 2cm) (condition of the seat width is sw + 2cm) (condition of the seat width is sw + 2cm) (condition of the seat width is sw + 2cm) (condition of the seat width is sw + 2cm) (condition of the seat width is sw + 2cm)	230 315
Sideguards LRF040107 ○ Sideguard, composite, re LRF040102 □ Sideguard, aluminium, cc LRF040103 □ Sideguard, aluminium, fe LRF040104 □ Sideguard, carbon fibre, FRAME LRF010010 ○ Frame FF 75 ° (integrate LRF010011 ○ Frame FF 85 ° (integrate LRF010015 □ Frame SA (removable fo LRF090100 ● Tie down brackets for tra CENTRE OF GRAVI COG23 ○ Centre of gravity 2.3cm COG43 ○ Centre of gravity 4.3cm COG63 ○ Centre of gravity 6.3cm COG63 ○ Centre of gravity 8.3cm	(not in combination with armrest) emovable, 21 cm high (31cm long), black cold weather protection (in frame colour) ender, cold weather protection (in frame colour) fender, cold weather protection (black) (effective seat width is sw + 2cm) (effective seat width is sw + 2cm) (effective seat width is sw + 2cm) (condition of the seat width is sw + 2cm) (condition of the seat width is sw + 2cm) (condition of the seat width is sw + 2cm) (condition of the seat width is sw + 2cm) (condition of the seat width is sw + 2cm) (condition of the seat width is sw + 2cm) (condition of the seat width is sw + 2cm) (condition of the seat width is sw + 2cm) (condition of the seat width is sw + 2cm) (condition of the seat width is sw + 2cm) (condition of the seat width is sw + 2cm) (condition of the seat width is sw + 2cm) (condition of the seat width is sw + 2cm) (condition of the seat width is sw + 2cm) (condition of the seat width is sw + 2cm) (condition of the seat width is sw + 2cm) (condition of the seat width is sw + 2cm) (condition of the seat width is sw + 2cm) (condition of the seat width is sw + 2cm) (condition of the seat width is sw + 2cm) (condition of the seat width is sw + 2cm) (condition of the seat width is sw + 2cm) (condition of the seat width is sw + 2cm) (condition of the seat width is sw + 2cm) (condition of the seat width is sw + 2cm) (condition of the seat width is sw + 2cm) (condition of the seat width is sw + 2cm)	230 315
LRF040107 ○ Sideguard, composite, re LRF040102 □ Sideguard, aluminium, co LRF040103 □ Sideguard, aluminium, fe LRF040104 □ Sideguard, carbon fibre, FRAME LRF010010 ○ Frame FF 75 ° (integrate LRF010011 ○ Frame FF 85 ° (integrate LRF010015 ○ Frame SA (removable fo LRF010015 ○ Tie down brackets for tra CENTRE OF GRAVI COG23 ○ Centre of gravity 2.3cm COG63 ○ Centre of gravity 6.3cm COG63 ○ Centre of gravity 8.3cm	emovable, 21 cm high (31cm long), black old weather protection (in frame colour) ender, cold weather protection (in frame colour) fender, cold weather protection (black) d footrest) msportation	315
LRF040102 □ Sideguard, aluminium, co LRF040103 □ Sideguard, aluminium, fe LRF040104 □ Sideguard, carbon fibre, FRAME LRF010010 ○ Frame FF 75 ° (integrate LRF010011 ○ Frame FF 85 ° (integrate LRF010015 ○ Frame SA (removable fo LRF010015 ○ Tie down brackets for tra CENTRE OF GRAVI COG23 ○ Centre of gravity 2.3cm COG43 ○ Centre of gravity 4.3cm COG63 ○ Centre of gravity 6.3cm COG63 ○ Centre of gravity 8.3cm	bold weather protection (in frame colour) conder, cold weather protection (in frame colour) fender, cold weather protection (black) d footrest) d footrest) d footrest) d footrest) d footrest) conder, cold weather protection (black) (LLL from 34cm) d footrest) d footrest) nsportation	315
LRF040103 □ Sideguard, aluminium, fe LRF040104 □ Sideguard, carbon fibre, FRAME LRF010010 ○ Frame FF 75 ° (integrate LRF010011 ○ Frame FF 85 ° (integrate LRF010016 □ Frame FF 85 ° (integrate LRF010015 ○ Frame SA (removable fo LRF090100 ● Tie down brackets for tra CENTRE OF GRAVI COG23 ○ Centre of gravity 2.3cm COG43 ○ Centre of gravity 4.3cm COG63 ○ Centre of gravity 6.3cm COG63 ○ Centre of gravity 8.3cm	d footrest)	315
LRF040104 □ Sideguard, carbon fibre, FRAME LRF010010 ○ Frame FF 75 ° (integrate LRF010011 ○ Frame FF 85 ° (integrate LRF010016 □ Frame FF 85 ° (integrate LRF010015 ○ Frame SA (removable fo LRF090100 ● Tie down brackets for tra CENTRE OF GRAVI COG23 ○ Centre of gravity 2.3cm COG43 ○ Centre of gravity 4.3cm COG63 ○ Centre of gravity 6.3cm COG63 ○ Centre of gravity 8.3cm	d footrest) d some sade width is sw + 2cm)	
FRAME	d footrest) (LLL from 34cm) d footrest) d footrest), inset (2cm on each side), active otrest) nsportation	395
LRF010010 ○ Frame FF 75 ° (integrate LRF010011 ○ Frame FF 85 ° (integrate LRF010016 □ Frame FF 85 ° (integrate LRF010015 ○ Frame SA (removable fo LRF090100 ● Tie down brackets for tra CENTRE OF GRAVI COG23 ○ Centre of gravity 2.3cm COG43 ○ Centre of gravity 4.3cm COG63 ○ Centre of gravity 6.3cm COG63 ○ Centre of gravity 8.3cm	d footrest) d footrest), inset (2cm on each side), active otrest) nsportation	
LRF010011 ○ Frame FF 85 ° (integrate LRF010016 □ Frame FF 85 ° (integrate LRF010015 ○ Frame SA (removable fo LRF090100 ● Tie down brackets for tra CENTRE OF GRAVI COG23 ○ Centre of gravity 2.3cm COG43 ○ Centre of gravity 4.3cm COG63 ○ Centre of gravity 6.3cm COG63 ○ Centre of gravity 8.3cm	d footrest) d footrest), inset (2cm on each side), active otrest) nsportation	
LRF010016 ☐ Frame FF 85 ° (integrate LRF010015 ☐ Frame SA (removable fo LRF090100 ● Tie down brackets for tra CENTRE OF GRAVI COG23 ☐ Centre of gravity 2.3cm COG43 ☐ Centre of gravity 4.3cm COG63 ☐ Centre of gravity 6.3cm COG63 ☐ Centre of gravity 8.3cm	d footrest), inset (2cm on each side), active otrest) insportation	
LRF010015 ○ Frame SA (removable fo LRF090100 ● Tie down brackets for trace CENTRE OF GRAVICOG23 ○ Centre of gravity 2.3cm ○ Centre of gravity 4.3cm ○ Centre of gravity 6.3cm ○ Centre of gravity 8.3cm ○ Centre of gravity 8.3cm	otrest) insportation	
Proposition CENTRE OF GRAVI COG23	nsportation	
CENTRE OF GRAVI COG23 O Centre of gravity 2.3cm COG43 O Centre of gravity 4.3cm COG63 O Centre of gravity 6.3cm COG63 O Centre of gravity 8.3cm	•	
COG23 O Centre of gravity 2.3cm COG43 O Centre of gravity 4.3cm COG63 O Centre of gravity 6.3cm COG83 O Centre of gravity 8.3cm	TY (COG) measured from front of back post; choose only one option	
COG43 O Centre of gravity 4.3cm COG63 O Centre of gravity 6.3cm COG83 O Centre of gravity 8.3cm		
COG63 O Centre of gravity 6.3cm COG83 O Centre of gravity 8.3cm		
COG83 O Centre of gravity 8.3cm		
Frame accessories		
<i>LRF010500</i> □ Handbike axle	(1)	365
<i>LRF</i> 090010 □ Transit wheels	(Not with crutch holder, tip assist and anti tip)	235
Tip assist (step tube) &	Crutch holder (choose either tip assist or anti-tip tubes, not both)	
<i>LRF090001</i> □ Tip assist, left	<i>LRF090002</i> □ Tip assist, right	35
<i>LRF</i> 090003 □ Tip assist, pair		70
LRF090009 □ Crutch holder, loop	(only in combination with tip assist)	80
Anti-tip tubes, swing-av	way (choose either tip assist or anti- tip tubes, not both)	
LRF090036 O Anti-tip tubes, aluminium	, lightweight, swing-away (forwards), pair	95
LRF090004 □ Anti-tip tubes, swing-awa	y, left LRF090005 □ Anti-tip tubes, swing-away, right	125
LRF090006 □ Anti-tip tubes, swing-awa	ıy, pair	195
(1) (max 100 kg user weight; not with drumbrake	, crutch holder, tip assist, anti tip, wheel drive)	

			£
		PREPARATION FOR ATTITUDE ADD-ON BIKE - only with FF-Frame	
.RF090211		Preparation for ATTITUDE, w/o ATTITUDE order (docking pins assembled)	125
.RF090212	0	Preparation for ATTITUDE, with ATTITUDE order (docking pins assembled; ATTITUDE order seperately)	
		EMPLIE OF FEE DUNDLING	
TMO000101		EMPULSE F55 BUNDLING With F55 and a maturage of the subscilled in	
EMO000101	0	With F55 order, not mounted to the wheelchair (Please use separate OF to order the F55.) With F55 order, mounted to the wheelchair (Please use separate OF to order the F55.)	
EMO000102	0	With F55 order, mounted to the wheelchair (Please use separate OF to order the F55.)	
		HANGERS & FOOTPLATES	
.RF050002	0	Hanger angle 70°	
RF050001	0	Hanger angle 80°	
RF050041	0	Hanger angle 90° (not with 6" & 7" castor)	
RF050008	0	Hanger, aluminium, swing-away, pair	
RF050006	0	Hanger, aluminium, swing-away, LH LRF050007 O Hanger, aluminium, swing-away, RH	
		Composite hanger	
RF050002	0	Hanger angle 70°	
.RF050001	0	Hanger angle 80°	
RF050005	0	Hanger, composite, swing-away, pair	
RF050003	0	Hanger, composite, swing-away, LH LRF050004 O Hanger, composite, swing-away, RH	
		Elevating Legrest (ELR)	
RF050011		Hanger, aluminium, flip-up (0° - 90°), swing-away, pair (1) (from seat width 38cm)	330
.RF050009			155
.RF050010		Hanger, aluminium, flip-up (0° - 90°), swing-away, RH (1)	155
		Footplate (when SA front selected)	.00
RF050020	•	Footplates, divided, composite, angle-adjustable, flip-up (sideways), heel loop, black (2)	
RF050050		Footplates, divided, aluminium, angle-adjustable, flip-up (sideways), heel loop, black (from LLL 35cm)	150
			150
.RF050102		Footboard, platform, aluminium, angle-adjustable, flip-up (sideways), heel loop, black (3)	
		LRF050126 ☐ Swing-away mechanism for platform footboard (from LLL 34cm)	100
		LRF050062 ☐ Locking system, platform footplate, aluminium	75
		Platform footrest, angle adjustable (only for seat width 32 to 50cm)	
.RF050131		Footboard, platform, lightweight, composite, angle & depth-adjustable flip up, calf strap black (4)	195
.RF050132		Footboard, platform lightweight, carbon fibre, angle &depth-adjustable flip-up, calf strap, black (4)	395
.RF050127		Adjustable side protection, to create a side-stop on the footboard (only in combination with Platform)	30
		Footrest (only with fixed front frame) (not with hanger; lower leg length between 36 - 52.5cm)	
.RF050025	0	Footboard, platform, lightweight, composite, angle and depth-adjustable, calf strap, black	
RF050024		Footboard, platform, lightweight, aluminum, angle and depth-adjustable, calf strap, frame colour	195
.RF050127		Adjustable side protection, to create a side-stop on the footboard (only with LIR050025/050024/050032)	30
		LOWER LEG LENGTH (LLL in cm) (Attention: LLL has to be 25 mm lower than seat height front)	
	0	33 O 34 O 35 O 36 O 37 O 38 O 39	
	0	40 O 41 O 42 O 43 O 44 O 45 O 46 O 47	
		FORK (compare with your choice on the first page)	
.RF080041	•	Castor fork, Aluminium, Black	
		LRF080042 O Colour Cast. Fork Silver	
		LRF080043 O Colour Cast. Fork Orange	
		CASTOR (compare with your choice on the first page)	
RF080301	0	Castor, solid (hard), rim: composite, black	
RF080302	0	Castor, solid (soft), rim: composite, black (only for 5" & 6" castors; max SH 520mm)	
.RF080305	0	Castor, pneumatic, rim: composite, black (only for 6" & 7" castors)	
		Castor with aluminium rim	
.RF080304		Castor, solid (hard), rim: aluminium (Only for 4" and 5")	105
.RF080304		Castor, solid (nard), rim: aluminium (Only for 4" and 5";) (Only for 4" and 5";)	105
000300			103
		Colour, rim: LRF080311 O Black LRF080315 O Blue	
1):		LRF080313 O Orange LRF080314 O Red in combination with platform footboard (2): pair; from LLL 33cm; only from SW 36cm	

			£
		REAR WHEELS (compare with your choice on the first page; choose only one wheel type)	
LRF070000	0	Without rear wheel	
LRF070001	0	Rear wheel, Universal, 36 spokes (silver), cross-wise spokes (only 22"/24")	
LRF070002	0	Rear wheel, Design, 36 spokes (silver), straight spokes (only 24")	
LRF070003		Rear wheel, Lightweight, 24 spokes (silver), straight spokes (max. user weight: 125 kg)	90
LRF070004		Rear wheel, Proton, 24 spokes (black), straight spokes (max. user weight: 100 kg)	250
LRF070005		Rear wheel, Spinergy, 18 spokes (black), straight spokes, hub: silver (only 24"/25")	495
LRF070008		Rear wheel, drum brakes, 36 spokes (silver), cross-wise spokes (only 22"/24")	425
LRF070009		Rear wheel, Mountain bike, 36 spokes (silver), straight spokes (only 24")	360
LRF070010		Mountain bike wheel, replacement kit incl. tyre (extra coarse profile) (only 24")	585
		TYRES (choose only one tyre type)	
LRF070107	•	Tyre, pneumatic, slick, Schwalbe One (only 24"/25")	115€
LRF070101	0	Tyre, pneumatic, fine profile, Schwalbe Right Run (only 22"/24")	
LRF070102	0	Tyre, puncture proof, tread (25" only with Proton, lightweight wheel)	
LRF070104		Tyre, pneumatic, puncture proof, tread, Schwalbe Marathon Plus Evolution (only 24"/25")	95
		HANDRIM	
LRF070202	0	Handrims, aluminium, anodised, silver	
LRF070201	0	Handrims, aluminium, powder-coated, clear	
LRF070204		Handrims, stainless steel, silver	100
LRF070203		Handrims, aluminium, powder-coated, coloured	
LRF070207		Handrims, Supergrip ® (22" only with universal and drum brake wheels)	250
LRF070208		Handrims, Maxgrepp ® (only 22"/24", only handrim mounting wide)	350
LRF070212		Handrims, Ellipse 3R, black (ergonomic handrims with rubber-strip, 24" and 25" only)	125
LRF070200	0	Without handrims	
		HANDRIM MOUNTING	
LRF070307	0	Handrim mount, super narrow (7 mm) (Only with 24" stainless steel)	
LRF070317	0	Handrim mount, narrow (17 mm) (not with Maxgrepp)	
LRF070327	0	Handrim mount, wide (27 mm)	
		HANDRIM COVER	
LRF070250		Handrim cover, Silicon (not with 25", Supergrip.Maxgrepp)	110
		WHEEL CAMBER (choose only one option; Armrests only with 0° & 1°)	
LRF070600	0	Camber 0° (no camber brackets provided)	
LRF070601	•	Camber 1° LRF070603 O Camber 3°	
LRF070602	0	Camber 2° LRF070604 O Camber 4°	
		SPOKE GUARDS (not with spinergy wheels, not with 25", not with mountain bike)	
LRF070831		Transparent LRF070820 □ Oriental LRF070827 □ Silk	150
LRF070822		Pool LRF070817 Hot Wheels	150
LRF070811		Feather <i>LRF070806</i> □ Chrome	150
LRF070814		Graffiti LRF070802 □ Basketball	150
		WHEEL LOCKS (choose only one option)	
LRF060001	0	Standard brake	
LRF060003		Compact brake	75
LRF060002		Knee-lever brake	95
LRF060010		Brake lever extension, knee-lever brake, fold-down	50

									Ī	£
	AC	CESSORIES	S							
LRF090000	•	Tool kit								
LRF090025		Air pump								20
LRF090024		High pressure	e pump (0	- 11 bar)						90
LRF090030		Back pack		<u> </u>						75
LRF090026		Mobile phone	pocket							55
	CO	LOURS (1)	Please co	nsult our col	lour cata	alogue to review your colour cl	noice			
		Frame	Handrim	Hub/rim	Fork	1	Frame	Handrim	Hub/rim	Fork
			75	220				75	220	
02 Brilliant Si	lver	0				29 Black	0			
03 Silver Mat	t	0				31 Matt Black	0			
06 Sun Yellov	w	0				32 Signal White	0			
14 Blue		0				33 Pink	0			
15 Brilliant M	arine	0				34 Dark Chocolate Metallic	0			
16 Matt Marir	ne	0				35 Skyblue	0			
19 Brilliant Pเ	urple	0				36 Cyan-Metallic	0			
21 Red Ruby	,	0				37 Mars red (Orange)	0			
22 Brilliant Re	ed	0				40 Kiwi	0			
23 Matt Red		0				41 Flamingo-Glitter	0			
24 Tutti Frutti	i Orar	ige O				42 Matt-Anthracite	0			
27 Graphite N	Metall	ic O				46 Mamba Green	0			
(1) Handrim	: only	with handrim o	colour pow	der coated; H	łub/rim:	only for universal wheel				
		STICKER (COLOUR	S						
LRF100550	•	Sticker colour	r - black							
LRF100551	0	Sticker colour	r - silver							
		ANODISE	COLOL	IR AXLE F	PLATE					
LRF100580	•	Axle plate an	odised, bla	ck						
LRF100581	0	Axle plate and	odised, siv	er						
LRF100582	0	Axle plate an	odised, ora	inge						
		24 " LIGHT	WEIGH	T WHEEL	COL	OURS				
	•	Black								
LRF100336		Anodised, ora	ange							
LRF100337		Anodised, blu	ıe							
LRF100338		Anodised, red	d							
	CO	MMENTS F	OR SPE	CIAL BUIL	.D					
								J : I		
								DUI	t <mark>4</mark> me	
Quickie I	Life	R - Basic	Price					£1,6	§95	
Option pric								£		
Packaging		transport						£		
Exclusive \	/AT							£		
VAT.								£		
Total Price	•							£		

Please follow this measuring method:

The following method is recommended on the basis of extensive practical experience. Deviations are possible in individual instances.

Seat width (SW):

a) For the user: Allow space between sideguard and hip on each side of the chair

(approx. 10 - 20 mm altogether)

b) On the wheelchair: From outside frame tube to outside frame tube.

Seat depth (SD):

a) For the user: When sitting upright: leave space for 2 - 3 fingers between

front edge of the seat upholstery and back of knee.

(approx. 30 - 60 mm). Care must be taken with adj. upholstery.

b) On the wheelchair: From back tube to front of seat upholstery.

Front seat height:

a) For the user: When sitting with 90° knee angle:

From back of knee to bottom of shoe sole.

b) On the wheelchair: From front of seat tube to the ground.

(min. 30 mm longer than user measurement) Remember to include the cushion height.

Rear seat height:

b) On the wheelchair: From back of seat tube to the ground.

Note: Max. seat height difference rear to front is 130 mm

Back height:

a) For the user: From the seat, including cushion, to be no more than 10 - 20 mm below the lower shoulder blade.

b) On the wheelchair: From back of seat tube to upper edge of backrest upholstery.

Note: The user's ability to sit upright has a major influence on the

back height and it can therefore differ considerably

Back angle: Important: The back height depends on the degree of disability.

 0° is the angle 90° to the ground. Negative angles are < 90°

and positive angles are > 90°.

				Seat Depth			
COG	380	400	420	440	460	480	500
40	×	X	×	>	~	~	~
60	×	×	×	×	~	~	~
70	×	×	×	×	~	~	~
80	×	×	×	×	×	~	~
90	×	×	×	×	×	~	~
100	×	×	×	×	×	×	V
110	×	×	×	×	×	×	V
120	×	×	×	×	×	×	×
130	×	×	×	×	×	×	×

SEAT UPHOLSTERY AND CUSHIONS



Seat cushion, cover with zipper, black



Seat cushion, climate membrane water-resistant, cover with zipper, black



Lap belt with buckle, metal



Jay Basic (picture shown without upholstery)



Jay Easy Visco (picture shown without upholstery)



Jay Easy Fluid (picture shown without upholstery)



Jay Lite

BACKREST



Backrest, angle-adjustable, lock when folded



Push handles long



Fold down push



Height adjustable push handles



EXO backrest sling



EXO PRO backrest sling

ARMREST AND SIDEGUARDS



Single post height adjustable armrest



Single-post sideguard, depth adjustable, tool height-adjustable



Sideguard composite detachable



Sideguard carbon with fender



Sideguard alu with fender



Desk amrest, height adjustable, short armpad(25cm)



Desk armrest, fixed height, short armpad(25cm)



Desk armrest without armpad

Frame



Life SA



Life FF 85°



Life FF 75°



Frame FF 85 ° (integrated footrest), inset (20

FRAME ACCESSORIES



Transit wheels



Tip assist




Crutch holder



Anti-tip swing away

FRAME ACCESSORIES







F

Hanger Angle 70°/80°



Elevating legrest



Amputee Support Pad



Platform footplate lightweight angle & depth adjustable composite flip up



Divided footplate composite



Divided footplate aluminium



Platform, angle and depth adjustable;flip up, aluminium with locking system

FORKS



Fork Aluminium, black, orange & silver

REAR WHEELS



Universal cross spoked



Design wheel



Lightweight wheel



Spinergy wheel, 18 spokes



Drum brake wheel

TYRES



Right Run Tyre



Solid Tyre



Marathon Plus Evolution



Supergrip



Max Grepp



Ellipse 3R Handrim

WHEEL LOCKS



Knee lever wheel lock



Brake lever extension



Compact wheel lock



Standard brake

ACCESSORIES



Back pack



High pressure pump



Air pump



Mobile phone pocket

Anodized colour axle plate



Axle plate anodized, orange



Axle plate anodized, silver



Axle plate anodized, black

24 " LIGHT WEIGHT WHEEL COLOURS



Lightweight wheel, anodized orange



Lightweight wheel, anodized blue



Lightweight wheel, anodized red